



RECOMMENDED MINIMUM ISO FLUID CLEANLINESS LEVEL: 19/16/13  
 RECOMMENDED FLUID TYPE: HIGH QUALITY PETROLEUM BASE HYDRAULIC FLUID,  
 WITH A GOOD ANTI-WEAR ADDITIVE PACKAGE (ISO 46 OR ISO 68)

ESTIMATED DRY WEIGHT: 612 LB [277.6 KG]

- EXAMPLE FLUIDS:  
 -Parker DuraClean™  
 -MOBIL DTE 25 OR DTE 26  
 -TEXACO RANDO HD46 OR HD68  
 -SHELL TELLUS 46 OR 68

TOLERANCES  
UNLESS OTHERWISE SPECIFIED

X/X	±1/32
.X	±.030
.XX	±.015
.XXX	±.005
∠	±1°
125	±.030
∩	±.010
∥	±.010
○	±.002
⊙	±.005

THIS DRAWING IS THE PROPERTY OF AND  
 CONTAINS CONFIDENTIAL INFORMATION  
 PROPRIETARY TO HYSPECO INC. IT IS  
 TO BE USED ONLY FOR THE PURPOSE  
 FOR WHICH IT WAS PROVIDED. IT IS  
 NOT TO BE COPIED OR DISCLOSED TO  
 OTHERS AND, UPON REQUEST, RETURNED  
 TO HYSPECO INC.

**HYSPECO** PHONE: (800) 234-1041

HYPACK TPD FOUR STA. HPU (MODEL G)  
 ASSY#: A15G0005

DATE 2/14/2024	SCALE 1/12	REVISION
DRAWN BY GWM	SHEET 1 OF 1	<b>B</b>
CHECKED BY	DRAWING No. A15G0005-L	
APPROVED BY		

REV	DATE	CHANGE	BY
REVISION HISTORY			