



RECOMMENDED MINIMUM ISO FLUID CLEANLINESS LEVEL: 19/16/13
 RECOMMENDED FLUID TYPE: HIGH QUALITY PETROLEUM BASE HYDRAULIC FLUID,
 WITH A GOOD ANTI-WEAR ADDITIVE PACKAGE (ISO 46 OR ISO 68)

ESTIMATED DRY WEIGHT: 659 LB [298.9 KG]

- EXAMPLE FLUIDS:
 -Parker DuraClean™
 -MOBIL DTE 25 OR DTE 26
 -TEXACO RANDO HD46 OR HD68
 -SHELL TELLUS 46 OR 68

REV	DATE	CHANGE	BY
REVISION HISTORY			

TOLERANCES UNLESS OTHERWISE SPECIFIED

X/X	±1/32
.X	±.030
.XX	±.015
.XXX	±.005
∅	±.010
∅	±.002
∅	±.005

THIS DRAWING IS THE PROPERTY OF AND CONTAINS CONFIDENTIAL INFORMATION PROPRIETARY TO HYSPECO INC. IT IS TO BE USED ONLY FOR THE PURPOSE FOR WHICH IT WAS PROVIDED. IT IS NOT TO BE COPIED OR DISCLOSED TO OTHERS AND, UPON REQUEST, RETURNED TO HYSPECO INC.

HYSPECO PHONE: (800) 234-1041

HYPAK TPD FOUR STA. HPU (MODEL G)
 ASSY#: A20G0006

DATE 2/14/2024	SCALE 1/12	REVISION
DRAWN BY GWM	SHEET 1 OF 1	B
CHECKED BY	DRAWING No. A20G0006-L	
APPROVED BY		