



RECOMMENDED MINIMUM ISO FLUID CLEANLINESS LEVEL: 19/16/13

ESTIMATED DRY WEIGHT: 924 LB [419.1 KG]

RECOMMENDED FLUID TYPE: HIGH QUALITY PETROLEUM BASE HYDRAULIC FLUID,
WITH A GOOD ANTI-WEAR ADDITIVE PACKAGE (ISO 46 OR ISO 68)

- EXAMPLE FLUIDS:
- Parker DuraClean™
 - MOBIL DTE 25 OR DTE 26
 - TEXACO RANDO HD46 OR HD68
 - SHELL TELLUS 46 OR 68

TOLERANCES
UNLESS OTHERWISE SPECIFIED

x/x	±1/32
.x	±.030
.xx	±.015
.xxx	±.005
∠	±1°
∠	±.030
∠	±.010
∠	±.010
∠	±.002
∠	±.005

THIS DRAWING IS THE PROPERTY OF AND
CONTAINS CONFIDENTIAL INFORMATION
PROPRIETARY TO HYSPECO INC. IT IS
TO BE USED ONLY FOR THE PURPOSE
FOR WHICH IT WAS PROVIDED. IT IS
NOT TO BE COPIED OR DISCLOSED TO
OTHERS AND, UPON REQUEST, RETURNED
TO HYSPECO INC.

HYSPECO PHONE: (800) 234-1041

HYPAK TPD SGL STA. HPU (MODEL F)
ASSY#: C25F0001

DATE 2/19/2024	SCALE 1/12	REVISION
DRAWN BY GWM	SHEET 1 OF 1	B
CHECKED BY	DRAWING No. C25F0001-L	
APPROVED BY		

REV	DATE	CHANGE	BY
REVISION HISTORY			